

LISTING OF THE CLAIMS

The listing of the claims provided below replaces all prior versions of the claims in the application. Please amend the claims as follows:

1-58. (Canceled)

59. (Withdrawn) A child seat comprising:
a base having a seating surface; and
an object holder pivotally attached to the base to pivot between an extended, in-use position and a retracted, storage position, the object holder having a cavity for receiving objects; wherein when the object holder is in the retracted, storage position, a first portion of the cavity extends beyond an outer side surface of the base, and a second portion of the cavity does not extend beyond the outer side surface of the base.

60-62. (Canceled)

63. (Withdrawn) The child seat of claim 59 further comprising a second object holder attached to the base.

64. (Currently Amended) A child seat for seating a child within a vehicle, comprising:
a base having a seating surface and an outer side surface; and
an object holder including an end portion that forms a cavity for receiving and holding an object;

wherein the object holder is attached to the base such that the object holder is movable in and out of the base between an extended, in use position and a fully retracted, storage position;

wherein, when the object holder is in the fully retracted, storage position, the object holder can be retracted no further into the base, and ~~only a portion of the object holder is within the base such that a first portion of the cavity remains extended from the base and a second portion of the cavity is retracted within the base~~ a first part of the end portion is received within the base and located under the seating surface with one section of the cavity inaccessible as a gripping surface and a second part of the end portion extends beyond the outer side surface of the base with another section of the cavity accessible as a gripping surface;

wherein the child seat is configured for placement on a seat of the vehicle, and wherein the child seat has a belt path configured to receive and locate relative to the child a lapbelt of a restraint system of the vehicle.

65. (Withdrawn) The child seat of claim 64, wherein the object holder is pivotally attached to the base.

66. (Previously Presented) The child seat of claim 64, wherein the object holder is slidably attached to the base.

67. (Previously Presented) The child seat of claim 64, wherein the object holder includes an extension slidably connected to the base and positioned under the seating surface.

68. (Previously Presented) The child seat of claim 67, wherein the extension includes a slot, and the base includes a post positioned in the slot to limit a sliding motion of the object holder.

69. (Previously Presented) The child seat of claim 64, further comprising a second object holder attached to the base.

70. (Canceled)

71. (Previously Presented) The child seat of claim 67, wherein the cavity is at a distal end of the extension.

72. (Withdrawn) A child seat comprising:
a seat portion including a base having a seating surface; and
an object holder attached to the base and movable between an extended, in use position and a retracted, storage position;
wherein the object holder includes a cavity for receiving objects;
wherein the cavity is partially under the seating surface in the retracted, storage position,
and
wherein the object holder is pivotally attached to the base to pivot between the extended, in use position and the retracted, storage position.

73-74. (Canceled)

75. (Currently Amended) A child seat for seating a child within a vehicle, comprising:

a base having a seating surface and an outer side surface; and

first and second object holders attached to the base, each of the first and second object holders including an end portion that forms a cavity for receiving and holding an object;

wherein each of the first and second object holders is movable, independently of the other, between an extended, in use position and a fully retracted, storage position;

wherein, when in the fully retracted, storage position, each respective object holder can be retracted no further into the base, and ~~only a portion of the respective object holder is within the base such that a first portion of the cavity remains extended from the base and a second portion of the cavity is retracted within the base~~ a first part of the end portion of each respective object holder is received within the base and located under the seating surface with a first section of the cavity inaccessible as a gripping surface and a second part of the end portion of each respective object holder extends beyond the outer side surface of the base with another section of the cavity accessible as a gripping surface.

76. (Previously Presented) The child seat of claim 75, wherein the first and second object holders are attached to a front portion of the base.

77. (Previously Presented) The child seat of claim 76, wherein the first and second object holders are attached to opposite sides of the front portion of the base.

78. (Previously Presented) The child seat of claim 75, wherein the first and second object holders are attached to opposite sides of the base.